

Marathon Installation Checklist

Congratulations on the purchase of your Marathon Water Heater. This water heater will provide you a lifetime of energy savings if you follow just a few simple steps:

- Do not apply heat to the top union nuts.** Build a short assembly with male and female adapters, and solder separate from heater. After they cool, screw them onto the tee, and brass nipple. Damage caused by applying heat will void the warranty.
- Do not over-tighten the union nuts.** There is a flat neoprene washer on the inside of these unions and “snugging” with water pump pliers is sufficient for a good seal.
- Install a drain line on the temperature/pressure relief valve.** Code requires the drain line to be plumbed to within 6” of the floor.
- Fill the tank with water before turning on power.** Vent air out of a faucet to make sure no air pockets remain before energizing. Continuous water **MUST** come out of hot tap before energizing
- Be sure to fill out and mail the warranty registration card located in your owner’s packet and mail it directly to Water Heater Innovations, Inc. at the address provided.**
- If you have questions, please refer to the Quick Start Guide, Owner’s Use & Care Manual, or call your utility for guidance.** More product information may also be found at www.marathonheaters.com
- Your Marathon has a 6-year (from date of manufacture) parts and labor warranty to reimburse service costs. Service calls to replace a part are limited to a \$75 reimbursement (diagnostic time is not included) and tank replacement is limited to a \$100 reimbursement. Service must be performed by a professional contractor to receive labor reimbursement. (please contact our Member Solutions group at #800-698-2007 for details)**